







SOLID OAK FLOORING 21MM

SIDE PROFILE				
SIZES	W: VARIABLE	H: 21mm	L: 600-2200mm	
PROFILE	TONGUE AND GROOVE			
BEVEL	1.5mm 45° BEVEL ALONG LONG EDGES (GO2)			
WEIGHT PER M²	14.36 KG/M ²			
CLASS OF USE		CLASS 34 (EN ISO 10874)		
HARDNESS RATING	BRINELL RATING BETWEEN 2.4 TO 3.4			
UPEC RATING	U3sP3E1C0			
DENSITY	650 TO 800kg/M ³ (AVERAGE 750kg/M ³)			
SHRINKAGE	RADIAL 0.16 - TANGENTIAL 0.33			
TOLERANCES	FLUSH: +/- 0.5mm	SQUARENESS: +/- 0.3mm		
HUMIDITY LEVEL	10% (+/-2%) ON FACTORY EXIT			
FIRE RATING (EN 14342:2013)	UNFINISHED: DFL-S1 IN ACCORDANCE WITH EN 14342:2013			
	FINISHED: CFL-S1 IN ACCORDANCE WITH EN 14342:2013			
THERMAL RESISTANCE	0.10 M ² K/W			
ORIGIN OF WOOD		100% OAK SOURCED FROM FRANCE		
MANUFACTURE ORIGIN	100% MADE IN FRANCE			
CERTIFICATIONS & LABELS	PEFC CERTIFICATE	PARQUET DE FRANCE	CE MARKING	HEALTH RATING
	 YES	 YES	 YES	 A+
FORMALDEHYDE EMISSION	E1 RATING IN ACCORDANCE WITH EN 717-1			
PENTACHLOROPHENOL CONTENT	LESS THAN OR EQUAL TO 5PPM			
UNDERFLOOR HEATING COMPATIBILITY	 NOT COMPATIBLE WITH UNDERFLOOR HEATING			
REVERSIBLE FLOORING	NON REVERSIBLE			
INSTALLATION TYPE	NAILED OR GLUED INSTALLATION			